



Typ type	Abmessungen dimensions			$\Phi_i$ Prüflöhre $\Phi_i$ control gauge mm	Gewicht weight g	Bestellnummer order number
	D / mm	d / mm	l / mm			
HZ 5/2/200g	5 ± 0,3	2 ± 0,3	200 ± 3	6	≈ 14	407 052200 026
HZ 6/3/200g	6 ± 0,3	3 ± 0,3	200 ± 3	7	≈ 20	407 063200 026
HZ 7/3/200g	7 ± 0,3	3 ± 0,3	200 ± 3	8	≈ 29	407 073200 026
HZ 8/4/200g	8 ± 0,3	4 ± 0,3	200 ± 3	9	≈ 35	407 084200 026
HZ 9/4/200g	9 ± 0,3	4 ± 0,3	200 ± 3	10	≈ 48	407 094200 026
HZ 10/5/200g	10 ± 0,35	5 ± 0,3	200 ± 3	11	≈ 55	407 105200 026
HZ 11/5/200g	11 ± 0,35	5 ± 0,3	200 ± 3	12	≈ 70	407 115200 026
HZ 12/6/200g	12 ± 0,35	6 ± 0,3	200 ± 3	13	≈ 80	407 126200 026
HZ 13/6/200g	13 ± 0,35	6 ± 0,3	200 ± 3	14	≈ 100	407 136200 026
HZ 14/7/200g	14 ± 0,4	7 ± 0,3	200 ± 3	15	≈ 110	407 147200 026
HZ 15/7/200g	15 ± 0,4	7 ± 0,3	200 ± 3	16	≈ 130	407 157200 026
HZ 16/8/200g	16 ± 0,5	8 ± 0,3	200 ± 3	17	≈ 142	407 168200 026
HZ 17/8/200g	17 ± 0,5	8 ± 0,3	200 ± 3	18	≈ 166	407 178200 026
HZ 18/9/200g	18 ± 0,55	9 ± 0,3	200 ± 3	19	≈ 180	407 189200 026
HZ 19/9/200g	19 ± 0,55	9 ± 0,3	200 ± 3	20	≈ 205	407 199200 026
HZ 20/10/200g	20 ± 0,6	10 ± 0,35	200 ± 3	21	≈ 225	343 201020 026
HZ 21/10/200g	21 ± 0,6	10 ± 0,35	200 ± 3	22	≈ 250	343 201020 026
HZ 22/11/200g	22 ± 0,65	11 ± 0,35	200 ± 3	23	≈ 270	343 221120 026
HZ 23/11/200g	23 ± 0,75	11 ± 0,35	200 ± 3	24	≈ 300	343 231120 026E
HZ 24/12/200g	24 ± 0,75	12 ± 0,35	200 ± 3	25	≈ 325	343 241220 026E
HZ 25/12/200g	25 ± 0,75	12 ± 0,35	200 ± 3	26	≈ 355	343 251220 026E
HZ 26/13/200g	26 ± 0,8	13 ± 0,4	200 ± 3	27	≈ 380	343 261320 026E
HZ 28/14/200g	28 ± 0,85	14 ± 0,4	200 ± 3	29	≈ 435	343 281420 026E
HZ 30/15/200g	30 ± 0,9	15 ± 0,45	200 ± 3	31	≈ 500	343 301520 026E

Ferritmaterial K 2006 - andere Abmessungen auf Anfrage / ferrite grade K 2006 - further dimensions on request

All information given without liability. If you require further information about our products, do not hesitate to contact our representatives, or visit our homepage, [www.kaschke.de](http://www.kaschke.de).

**Kaschke Components GmbH**

Rudolf-Winkel-Straße 6 · 37079 Göttingen · Germany

Fon +49 (0) 5 51-50 58-6 · Fax +49 (0) 5 51-65 75 6

kaschke.de