



Typ type	Abmessungen dimensions		Φ_i Prüflehre Φ_i control gauge mm	Schlitze grooves	Gewicht weight g	Bestellnummer order number
	D / mm	l / mm				
S 4/200B	4 ± 0,3	200 ± 3	5	6	≈ 10	402 042004 026
S 5/200B	5 ± 0,3	200 ± 3	6	6	≈ 15	402 052004 026
S 6/200B	6 ± 0,3	200 ± 3	7	6	≈ 22	402 062004 026
S 7/200B	7 ± 0,3	200 ± 3	8	6	≈ 30	402 072004 026
S 8/200B	8 ± 0,3	200 ± 3	9	6	≈ 38	402 082004 026
S 9/200B	9 ± 0,3	200 ± 3	10	6	≈ 48	402 092004 026
S 10/200B	10 ± 0,35	200 ± 3	11	6	≈ 60	402 102004 026
S 11/200B	11 ± 0,35	200 ± 3	12	6	≈ 70	402 112004 026
S 12/200B	12 ± 0,35	200 ± 3	13	8	≈ 90	402 122004 026
S 13/200B	13 ± 0,35	200 ± 3	14	8	≈ 105	402 132004 026
S 14/200B	14 ± 0,4	200 ± 3	15	8	≈ 120	402 142004 026
S 15/200B	15 ± 0,4	200 ± 3	16	8	≈ 145	402 152004 026
S 16/200B	16 ± 0,5	200 ± 3	17	8	≈ 165	402 162004 026
S 17/200B	17 ± 0,5	200 ± 3	18	8	≈ 185	402 172004 026
S 18/200B	18 ± 0,55	200 ± 3	19	8	≈ 205	402 182004 026
S 19/200B	19 ± 0,55	200 ± 3	20	8	≈ 230	402 192004 026
S 20/200B	20 ± 0,6	200 ± 3	21	8	≈ 255	402 202004 026
S 21/200B	21 ± 0,6	200 ± 3	22	8	≈ 280	402 212004 026
S 22/200B	22 ± 0,65	200 ± 3	23	8	≈ 310	402 222004 026
S 23/200B	23 ± 0,75	200 ± 3	24	8	≈ 340	402 232004 026E
S 24/200B	24 ± 0,75	200 ± 3	25	8	≈ 370	402 242004 026E
S 25/200B	25 ± 0,75	200 ± 3	26	8	≈ 400	402 252004 026E
S 27/200B	27 ± 0,85	200 ± 3	28	8	≈ 480	402 272004 026E
S 30/200B	30 ± 0,9	200 ± 3	31	8	≈ 550	402 302004 026E
S 33/200B	33 ± 1,0	200 ± 3	34	8	≈ 660	402 332009 026E

Ferritmaterial K 2006 - andere Abmessungen auf Anfrage / ferrite grade K 2006 - further dimensions on request

All information given without liability. If you require further information about our products, do not hesitate to contact our representatives, or visit our homepage, www.kaschke.de.

Kaschke Components GmbH

Rudolf-Winkel-Straße 6 · 37079 Göttingen · Germany

Fon +49 (0) 5 51-50 58-6 · Fax +49 (0) 5 51-65 75 6

kaschke.de